

## Mobile Computer

# SUNMI L2K

- 2GB RAM+16GB ROM
- Increased expansion options support multiple accessories
- The industry-grade touch screen comes with a glove mode option
- Compatible with Honeywell/Zerba 1D and 2D barcode scanners
- Built-in small battery allows for replacement of the main battery without needing to turn off the mobile computer
- With this UHF trigger handle, SUNMI L2K can enhance your work efficiency by enabling the reading of multiple RFID tags.



1.5W  
loudspeaker



IP65  
rating



1.5M  
drop proof



SUNMI L2K  
Charging Base (optional)

SUNMI L2K  
UHF Trigger Handle (optional)

## SUNMI L2K Technical specifications

|  |  |   |   |  |
|--|--|---|---|--|
| <b>OS</b><br>Android 7.1<br>SUNMI OS                                   | <b>CPU</b><br>Qualcomm Snapdragon<br>quad-core 1.4GHz                | <b>Memory</b><br>16GB ROM+2GB RAM                               | <b>Display</b><br>4" WVGA 800x480,IPS<br>Multi touch,<br>Support glove mode   | <b>Adapter</b><br>Input:Type-C<br>Output:DC 5V/2A                            |
| <b>Wi-Fi</b><br>2.4G/5G<br>Support IEEE 802.11 a/b/<br>g/n             | <b>Bluetooth</b><br>Support BLE<br>Support Bluetooth 2.1/<br>3.0/4.2 | <b>Voice and Audio</b><br>1.5W<br>Two mic                       | <b>Port</b><br>1x Type-C USB<br>Support OTG<br>Support pogo pin   | <b>Key</b><br>Power button<br>Volume up/down Scan button<br>20 physical keys |
| <b>Battery</b><br>Removable polymer<br>Lithium battery<br>3.8V/5000mAh | <b>Communication</b><br>2G/3G/4G                                     | <b>1D/2D Scanner</b><br>Zebra 2D scanner<br>Honeywell(Optional) | <b>Camera</b><br>Rear: 13MP autofocus<br>Front: 2MP fixedfocus  | <b>NFC</b><br>ISO 14443 Type A/B<br>FeliCa and ISO 15693 cards               |
| <b>GPS</b><br>Support AGPS<br>Support GPS/Glonass/Beidou               | <b>SIM Card Slot</b><br>SIMx1<br>PSAMx1<br>Support 1.8V/3.0V         | <b>Size</b><br>159.4*73*19mm                                    | <b>Environmental</b><br>Operating temperature:-20°C-55°C<br>Storage temperature:-40°C-70°C<br>Sealing:IP65<br>Drop Specification:1.5m |  |

### Optional



**Trigger Handle**  
Support barcode reading



**UHF Trigger Handle**  
Support RFID tag reading



**Charging Base**  
Support L2K and UHF charging

## SUNMI L2K UHF Trigger Handle Technical specifications

|   |  |   |   |                                |
|---|--|---|---|--------------------------------|
| <b>RFID Engine</b><br>Impinj Indy R2000   | <b>Fastest Read Rate</b><br>>200 tags/sec  | <b>Longest Read Range</b><br>>10m   | <b>Antenna</b><br>Circularly polarized (4dBi) | <b>Battery</b><br>3.6V/3350mAh |
| <b>Protocols &amp; Standards</b><br>EPC Global UHF<br>Class 1 Gen 2/ ISO<br>18000-6C/ ISO<br>18000-6B | <b>Frequency Range</b><br>Chinese mainland<br>920-925MHz<br>American standard<br>902-928 MHz<br>European standard<br>865-868 MHz | <b>Environmental</b><br>Operating temperature:-10°C-50°C<br>Storage temperature:-40°C-70°C<br>Sealing:IP65<br>Drop Specification:1.5m |   |                                |

### Note:

1. Read rate and range depend on actual environments.
2. Real memory will be reduced due to a number of factors, and there are differences. Operating system also occupy part of memory.
3. Actual product specifications when sold take precedence over what may be listed at this catalogue; Any changes may be made without prior notification